
Soft Close Toilet Seat


CAM-TS1-RO, CAM-TS2-RO and CAM-TS3-SQ

For any technical or installation queries please contact Vado on 01934 745163.




VADC


CAM-TS1-RO CAM-TS2-RO CAM-TS3-SQ




Clip on the toilet seat.




Fit the plugs into the holes on the WC pan. Place each scew through the bracket, washer and screw into the plug.




Tighten the screws. **NOTE.** Don't fully tighten at this stage as adjustment is required.




Align the toilet seat with the ceramic bowl.




Tighten the screws in a clockwise direction (Do not overtighten).



Place the cover over each hinge.



Take off the toilet seat by lifting the seat while holding the release button.



Clip on the toilet seat and cover.

This toilet seat is finished to the highest standard. Due care needs to be taken to ensure the appearance is retained.

VADO recommends cleaning this product weekly with a soft damp cloth and mild soap solution.

VADO strongly advises against the use of all aggressive/corrosive cleaning products i.e. powders and liquids (including bleach). If these instructions are not followed, this may invalidate your guarantee in the event of a problem occurring.

Do not stand on the lid or ring of your toilet seat.

Replacement hinges, fixings, and washers can be obtained directly from VADO. Hinge Cover Codes: CAM-TSHP-CP - Chrome (Includes Fixings) CAM-TSHC-MB – Matt Black CAM-TSHC-MW – Matt White CAM-TSHC-SG – Satin Gold