
SPECIFICATION SHEET

COLLECTION: CELSIUS

PRODUCT CODE: CEL-149-1/2-C/P





The flow rate displayed is calculated using ideal system conditions. This result should only be taken as an indication as the flow rate may vary depending on the specific in-situ configuration.

VALVE TYPE

Exposed

STYLE

Round

ORIENTATION

Vertical

NUMBER OF OUTLETS

1 Outlet

HANDLES

2 Handle

WITH ALL-FLOW FUNCTION

No

WITH INTEGRATED DIVERTER

Νo

COMPATIBLE WITH STUDFAST

No

WITH BLEED VALVE FOR SYSTEM FLUSH ON

INSTALLATION

No



www.vado.com

WHERE INSPIRATION FLOWS



SPECIFICATION SHEET

COLLECTION: CELSIUS

PRODUCT CODE: CEL-149-1/2-C/P

WITH SHOWER KIT

Νo

INCLUDES MORTAR / TILE GUARD

Νo

COMPATIBLE WITH EASY-FIX BRACKETS

Yes

WITH THERMOSTATIC TECHNOLOGY

Yes

CONNECTIONS / FITTINGS

3/4" x 1/2" x 50mm offset connectors

SPARE PARTS

thermostatic cartridge V-704-34S flow cartridge C-202-RTC

MOUNTING

Wall Mounted

PLUMBING SYSTEM SUITABILITY

Gravity System, Pumped System, Combination Boiler, Pressurised System

COLLECTION NAME

Celsius

FINISH

Chrome

MINIMUM OPERATING PRESSURE

0.2 Bar LP

MAXIMUM OPERATING PRESSURE

5.0 Bar HP





SPECIFICATION SHEET

COLLECTION: CELSIUS

PRODUCT CODE: CEL-149-1/2-C/P

FLOW RATE AT 3.0 BAR FLOW PRESSURE

21 l/min

GUARANTEE

15 Year Guarantee

tel: 01934 744466 email: sales@vado.com www.vado.com






TECHNICAL DRAWING

COLLECTION: CELSIUS

PRODUCT CODE: CEL-149-1/2-C/P





www.vado.com



