
# SPECIFICATION SHEET

COLLECTION: GEO

PRODUCT CODE: GEO-142/PR-3/4-C/P





The flow rate displayed is calculated using ideal system conditions. This result should only be taken as an indication as the flow rate may vary depending on the specific in-situ configuration.

# TAP TYPE

Stop Valve

### PLUMBING SYSTEM SUITABILITY

Gravity System, Pumped System, Combination Boiler, Pressurised System

### MOUNTING

Deck Mounted, Wall Mounted

### DECK HOLE DRILL DIAMETER

33mm

### SPARE PARTS

cold ceramic cartridge C-302-RTC hot ceramic cartridge C-302-LTC  $\,$ 

# HANDLES

2 Handle

### **CONNECTIONS / FITTINGS**

3/4" x 10mm thread length male inlet 3/4" x 10mm thread length male outlet

# INSTALLATION TOLERANCES

min-max wall mount 25mm min-max bath thickness 6-25mm

## **VALVE TYPE**

Concealed





# SPECIFICATION SHEET

COLLECTION: GEO

PRODUCT CODE: GEO-142/PR-3/4-C/P

### **COLLECTION NAME**

Geo

**FINISH** 

Chrome

MINIMUM OPERATING PRESSURE

0.2 Bar LP

MAXIMUM OPERATING PRESSURE

5.0 Bar HP

GUARANTEE

15 Year Guarantee

tel: 01934 744466 email: sales@vado.com www.vado.com

WHERE INSPIRATION FLOWS


TAPS | SHOWERS | FURNITURE



# TECHNICAL DRAWING

COLLECTION: GEO

PRODUCT CODE: GEO-142/PR-3/4-C/P



tel: 01934 744466 email: sales@vado.com

www.vado.com



