
SPECIFICATION SHEET

COLLECTION: KNURLED ACCENTS PRODUCT CODE: IND-T148/2-H-BRGK





The flow rate displayed is calculated using ideal system conditions. This result should only be taken as an indication as the flow rate may vary depending on the specific in-situ configuration.

SHOWER TYPE

Shower Valve

VALVE TYPE

Concealed

ORIENTATION

Horizontal

NUMBER OF OUTLETS

1 Outlet

WITH ALL-FLOW FUNCTION

Yes

WITH INTEGRATED DIVERTER

No

COMPATIBLE WITH STUDFAST

Yes

WITH BLEED VALVE FOR SYSTEM FLUSH ON INSTALLATION

No

WITH SHOWER KIT

No

tel: 01934 744466 email: sales@vado.com

www.vado.com

WHERE INSPIRATION FLOWS



SPECIFICATION SHEET

COLLECTION: KNURLED ACCENTS PRODUCT CODE: IND-T148/2-H-BRGK

INCLUDES MORTAR / TILE GUARD

Yes

COMPATIBLE WITH EASY-FIX BRACKETS

No

WITH THERMOSTATIC TECHNOLOGY

Yes

INSTALLATION TOLERANCES

min-max wall mount 75-100mm optimum installation depth 87mm

CONNECTIONS / FITTINGS

2 x 3/4" female inlets / 2 x 3/4" female outlets

SPARE PARTS

thermostatic cartridge V-704-34S diverter cartridge FL-802-33/2MX

MOUNTING

Wall Mounted

PLUMBING SYSTEM SUITABILITY

Gravity System, Pumped System, Combination Boiler, Pressurised System

COLLECTION NAME

Knurled Accents

FINISH

Brushed Gold

MINIMUM OPERATING PRESSURE

0.2 Bar LP (Shower) / 1.0 Bar MP (Bath)

MAXIMUM OPERATING PRESSURE

5.0 Bar HP

tel: 01934 744466 email: sales@vado.com www.vado.com





SPECIFICATION SHEET

COLLECTION: KNURLED ACCENTS PRODUCT CODE: IND-T148/2-H-BRGK

GUARANTEE

15 Year Guarantee

tel: 01934 744466 email: sales@vado.com www.vado.com


WHERE INSPIRATION FLOWS


TAPS | SHOWERS | FURNITURE



TECHNICAL DRAWING

COLLECTION: KNURLED ACCENTS PRODUCT CODE: IND-T148/2-H-BRGK







www.vado.com



