


SPECIFICATION SHEET

COLLECTION: GEO

PRODUCT CODE: GEO-135/NS-3/4-C/P



TAP TYPE

Bath Shower Mixer

PLUMBING SYSTEM SUITABILITY

Pumped System, Combination Boiler, Pressurised System

HOLES

4 Hole

MOUNTING

Deck Mounted

WITH INTEGRATED DIVERTER

No

WITH EASY-FIT BRACKETS

No

WITH SHOWER KIT

Yes

WITH THERMOSTATIC TECHNOLOGY

No

FOR USE WITH BATH FILLER WASTE AND OVERFLOW

Yes

tel: 01934 744466
email: sales@vado.com
www.vado.com

WHERE INSPIRATION FLOWS
TAPS | SHOWERS | FURNITURE



SPECIFICATION SHEET

COLLECTION: GEO

PRODUCT CODE: GEO-135/NS-3/4-C/P

MINIMUM OPERATING PRESSURE

1.5 Bar MP

RECOMMENDED FLOW REGULATOR

FR-FLEXI/8-PLA

WITH BATH SPOUT

No

WITH AIR-INJECTION TECHNOLOGY

No

WITH WATER FLOW STRAIGHTENER

No

WITH WATER FLOW AERATOR

No

INSTALLATION TOLERANCES

min-max bath thickness 6mm - 38mm

CONNECTIONS / FITTINGS

1 x 1/2" x 3/8" x 200cm showerhose FxF 2 x 600mm x 3/4" flexihoses to inlets on valve

DECK HOLE DRILL DIAMETER

Valve: 37mm Diverter: 46mm Handset: 30mm

SPARE PARTS

cold ceramic cartridge C-302-RTC hot ceramic cartridge C-302-LTC

NOTES

3/4" ceramic disc 1/4 turn valves

FINISH

Chrome

SPECIFICATION SHEET

COLLECTION: GEO

PRODUCT CODE: GEO-135/NS-3/4-C/P

COLLECTION NAME

Geo

GUARANTEE

15 Year Guarantee

tel: 01934 744466
email: sales@vado.com
www.vado.com

WHERE INSPIRATION FLOWS
TAPS | SHOWERS | FURNITURE



TECHNICAL DRAWING

COLLECTION: GEO

PRODUCT CODE: GEO-135/NS-3/4-C/P

